



TYPES	I _F (A)	I _O (A)	V _{RWM} = V _{RRM} = V _R (V)	I _{FRM} (A)	I _{FSM} 10 ms (A)	V _F @ I _F = I _O (V)	I _R (mA)	Boitier Case
1,25 A / t_{amb} = 25°C t(v_j) = 150°C							t _{amb} = 150°C	
F 11 F 21 F 41 F 61 F 81 ou 1N 2616 F 101 ou 1N 2617 F 121	1,5 1,5 1,5 1,5 1,5 1,5 1,5	1,25 1,25 1,25 1,25 1,25 1,25 1,25	100 200 400 600 800 1000 1200	4 4 4 4 4 4 4	30 30 30 30 30 30 30	1,2 1,2 1,2 1,2 1,2 1,2 1,2	1 1 1 1 1 1 1	DO 13 métal.
2 A / t_{amb} = 25°C t(v_j) = 175°C							t _{amb} = 150°C	
F 12 F 22 F 42 F 62 F 82 F 102	2,4 2,4 2,4 2,4 2,4 2,4	2 2 2 2 2 2	100 200 400 600 800 1000	6,5 6,5 6,5 6,5 6,5 6,5	70 70 70 70 70 70	1,2 1,2 1,2 1,2 1,2 1,2	1 1 1 1 1 1	DO 13 métal.
3 A / t_{amb} = 50°C t(v_j) = 150°C							t _{amb} = 25°C	
BY 251 BY 252 BY 253 BY 254 BY 255	3,4 3,4 3,4 3,4 3,4	3 3 3 3 3	200 400 600 800 1300	20 20 20 20 20	100 100 100 100 100	1,1 1,1 1,1 1,1 1,1	0,02 0,02 0,02 0,02 0,02	DO 27 plastique plastic
3 A / t_{amb} = 80°C t(v_j) = 150°C I²t = 50 A²s							t _{amb} = 100°C	
BYW 17- 100 BYW 17- 200 BYW 17- 400 BYW 17- 600 BYW 17- 800 BYW 17- 1000 BYW 17- 1200	3,4 3,4 3,4 3,4 3,4 3,4 3,4	3 3 3 3 3 3 3	100 200 400 600 800 1000 1200	10 10 10 10 10 10 10	240 240 240 240 240 240 240	1,2 1,2 1,2 1,2 1,2 1,2 1,2	0,25 0,25 0,25 0,25 0,25 0,25 0,25	AG plastique plastic
3 A / t_{case} = 150°C t(v_j) = 175°C I²t = 200 A²s						V _{FM} @ I _{FM} = 10 A	t _{case} = 150°C	
1N 1581, (R) 1N 1582, (R) 1N 1583, (R) 1N 1584, (R) 1N 1585, (R) 1N 1586, (R) 1N 1587, (R)	3,2 3,2 3,2 3,2 3,2 3,2 3,2	3 3 3 3 3 3 3	50 100 200 300 400 500 600	15 15 15 15 15 15 15	200 200 200 200 200 200 200	1,2 1,2 1,2 1,2 1,2 1,2 1,2	0,5 0,5 0,5 0,5 0,5 0,5 0,5	DO 4
4 A / t_{case} = 125°C t(v_j) = 150°C I²t = 200 A²s						V _{FM} @ I _{FM} = 13 A	t _{case} = 125°C	
G, P 504, (R) G, P 1004, (R) G, P 2004, (R) G, P 4004, (R) G, P 6004, (R) G, P 8004, (R) G, P 1104, (R) G, P 1204, (R)	5 5 5 5 5 5 5 5	4 4 4 4 4 4 4 4	50 100 200 400 600 800 1000 1200	20 20 20 20 20 20 20 20	200 200 200 200 200 200 200 200	1,2 1,2 1,2 1,2 1,2 1,2 1,2 1,2	3 3 3 3 3 3 3 3	DO 4 (G) S95a (P)
6 A / t_{amb} = 90°C t(v_j) = 150°C I²t = 800 A²s						V _{FM} @ I _{FM} = 20 A	t _{amb} = 100°C	
BY 214-50 BY 214-100 BY 214-200 BY 214-400	6,5 6,5 6,5 6,5	6 6 6 6	50 100 200 400	20 20 20 20	400 400 400 400	1,2 1,2 1,2 1,2	1 1 1 1	AG plastique plastic

n° de type : cathode au boitier

n° de type + suffixe R : anode au boitier.

type number : cathode to case

type number + suffix R : anode to case.