

225mW Surface Mount Switching Diode

multicomp^{PRO}

RoHS
Compliant



Features:

- Fast switching speed
- For general purpose switching applications
- High conductance
- Silicon epitaxial planar chip

Mechanical Data:

Epoxy	: UL94-V0 rated flame retardant
Case	: Molded plastic, SOT-23
Terminals	: Solder plated, solderable per MIL-STD-750, method 2026
Mounting position	: Any
Weight	: Approximated 0.008 gram

Max. Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified.

Parameter	Symbol	Value	Units
Reverse Voltage	V _R	75	V
Forward Current	I _F	200	mA
Peak Forward Surge Current	I _{FM}	500	mA
Non-Repetitive Peak Forward Surge Current	I _{FSM}	2 1	A
Thermal Characteristics			
Total Device Dissipation FR-5 Board ⁽¹⁾ , T _A = 25°C Derate above 25°C	P _D	225 1.8	mW mW/°C
Thermal Resistance Junction to Ambient	R _{θJA}	556	°C/W
Total Device Dissipation FR-5 Substrate ⁽²⁾ , T _A = 25°C Derate above 25°C	P _D	300 2.4	mW mW/°C
Thermal Resistance Junction to Ambient	R _{θJA}	417	°C/W
Operating Temperature Range	T _J	-55 to +150	°C
Storage Temperature Range	T _{STG}	-65 to +150	°C

⁽¹⁾ FR-5 = 1.0×0.75×0.062 in

⁽²⁾ Alumina = 0.4×0.3×0.024 in.9935% alumina

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro

multicomp^{PRO}

225mW Surface Mount Switching Diode


multicomp PRO

Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified.

Parameter	Symbol	Min.	Max.	Units
Reverse Breakdown Voltage (I _{BR} = 100µAdc)	V _{BR}	75	-	V
Reverse Voltage Leakage Current at V _R = 75V, T _J = 25°C at V _R = 25V, T _J = 150°C at V _R = 75V, T _J = 150°C	I _R	-	1 30 50	µA
Diode Capacitance (V _R = 0V, f = 1.0MHz)	C _D	-	2	pF
Reverse Recovery Time (I _F = I _R = 10mA, V _R = 5.0V DC, I _R (REC) = 1.0mA, R _L = 100Ω)	T _{RR}	-	6	ns
Forward Voltage at I _F = 1.0mA at I _F = 10mA at I _F = 50mA at I _F = 150mA	V _F	-	715 855 1000 1250	mV

SOT-23



Dimensions : Inches (Millimetres)

Part Number Table

Description	Part Number
Diode, High Speed, SOT-23	BAS16+

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro

multicomp PRO