

LM78XX

Series Voltage Regulators

General Description

The LM78XX series of three terminal regulators is available with several fixed output voltages making them useful in a wide range of applications. One of these is local on card regulation, eliminating the distribution problems associated with single point regulation. The voltages available allow these regulators to be used in logic systems, instrumentation, HiFi, and other solid state electronic equipment. Although designed primarily as fixed voltage regulators these devices can be used with external components to obtain adjustable voltages and currents.

The LM78XX series is available in an aluminum TO-3 package which will allow over 1.0A load current if adequate heat sinking is provided. Current limiting is included to limit the peak output current to a safe value. Safe area protection for the output transistor is provided to limit internal power dissipation. If internal power dissipation becomes too high for the heat sinking provided, the thermal shutdown circuit takes over preventing the IC from overheating.

Considerable effort was expended to make the LM78XX series of regulators easy to use and minimize the number of external components. It is not necessary to bypass the out-

put, although this does improve transient response. Input bypassing is needed only if the regulator is located far from the filter capacitor of the power supply.

For output voltage other than 5V, 12V and 15V the LM117 series provides an output voltage range from 1.2V to 57V.

Features


- Output current in excess of 1A
- Internal thermal overload protection
- No external components required
- Output transistor safe area protection
- Internal short circuit current limit
- Available in the aluminum TO-3 package

Voltage Range

LM7805C	5V
LM7812C	12V
LM7815C	15V

Connection Diagrams


Metal Can Package
TO-3 (K)
Aluminum



Bottom View
Order Number LM7805CK,
LM7812CK or LM7815CK


See NS Package Number KC02A

Plastic Package
TO-220 (T)



Top View
Order Number LM7805CT,
LM7812CT or LM7815CT
See NS Package Number T03B

Schematic



DS007746-1

Absolute Maximum Ratings (Note 3)

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/Distributors for availability and specifications.

Input Voltage

($V_O = 5V, 12V$ and $15V$) $35V$

Internal Power Dissipation (Note 1)

Internally Limited

Operating Temperature Range (T_A)

$0^\circ C$ to $+70^\circ C$

Maximum Junction Temperature

(K Package) $150^\circ C$

(T Package) $150^\circ C$

Storage Temperature Range

$-65^\circ C$ to $+150^\circ C$

Lead Temperature (Soldering, 10 sec.)

TO-3 Package K $300^\circ C$

TO-220 Package T $230^\circ C$

Electrical Characteristics LM78XXC (Note 2)

$0^\circ C \leq T_J \leq 125^\circ C$ unless otherwise noted.

Output Voltage			5V			12V			15V			Units	
Input Voltage (unless otherwise noted)			10V			19V			23V				
Symbol	Parameter	Conditions	Min	Typ	Max	Min	Typ	Max	Min	Typ	Max		
V_O	Output Voltage	$T_J = 25^\circ C, 5 \text{ mA} \leq I_O \leq 1A$	4.8	5	5.2	11.5	12	12.5	14.4	15	15.6	V	
		$P_D \leq 15W, 5 \text{ mA} \leq I_O \leq 1A$ $V_{MIN} \leq V_{IN} \leq V_{MAX}$	4.75		5.25	11.4 (7.5 $\leq V_{IN} \leq$ 20)		12.6 (14.5 $\leq V_{IN} \leq$ 27)	14.25		15.75 (17.5 $\leq V_{IN} \leq$ 30)	V	
ΔV_O	Line Regulation	$I_O = 500 \text{ mA}$	$T_J = 25^\circ C$	3	50		4	120		4	150	mV	
			ΔV_{IN}			(7 $\leq V_{IN} \leq$ 25)		14.5 $\leq V_{IN} \leq$ 30)		(17.5 $\leq V_{IN} \leq$ 30)		V	
		$I_O \leq 1A$	$0^\circ C \leq T_J \leq +125^\circ C$		50			120 (15 $\leq V_{IN} \leq$ 27)		150 (18.5 $\leq V_{IN} \leq$ 30)		mV	
			ΔV_{IN}			(8 $\leq V_{IN} \leq$ 20)						V	
ΔV_O	Load Regulation	$T_J = 25^\circ C$	$5 \text{ mA} \leq I_O \leq 1.5A$	10	50		12	120		12	150	mV	
			$250 \text{ mA} \leq I_O \leq 750 \text{ mA}$		25			60			75	mV	
			$5 \text{ mA} \leq I_O \leq 1A, 0^\circ C \leq T_J \leq +125^\circ C$			50		120			150	mV	
I_Q	Quiescent Current	$I_O \leq 1A$	$T_J = 25^\circ C$		8		8			8		mA	
			$0^\circ C \leq T_J \leq +125^\circ C$		8.5		8.5			8.5		mA	
ΔI_Q	Quiescent Current Change	$5 \text{ mA} \leq I_O \leq 1A$			0.5		0.5			0.5		mA	
		$T_J = 25^\circ C, I_O \leq 1A$			1.0		1.0			1.0		mA	
		$V_{MIN} \leq V_{IN} \leq V_{MAX}$				(7.5 $\leq V_{IN} \leq$ 20)	(14.8 $\leq V_{IN} \leq$ 27)		(17.9 $\leq V_{IN} \leq$ 30)			V	
V_N	Output Noise Voltage	$T_A = 25^\circ C, 10 \text{ Hz} \leq f \leq 100 \text{ kHz}$			40		75		90			μV	
		$f = 120 \text{ Hz}$	$I_O \leq 1A, T_J = 25^\circ C$ or $I_O \leq 500 \text{ mA}$ $0^\circ C \leq T_J \leq +125^\circ C$	62	80	55	72		54	70		dB	
			$V_{MIN} \leq V_{IN} \leq V_{MAX}$		62	55			54			dB	
R_O	Dropout Voltage Output Resistance	$T_J = 25^\circ C, I_{OUT} = 1A$			2.0		2.0		2.0			V	
		$f = 1 \text{ kHz}$			8		18		19			$m\Omega$	

Electrical Characteristics LM78XXC (Note 2) (Continued)

$0^{\circ}\text{C} \leq T_J \leq 125^{\circ}\text{C}$ unless otherwise noted.

Output Voltage			5V			12V			15V			Units
Input Voltage (unless otherwise noted)			10V			19V			23V			
Symbol	Parameter	Conditions	Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
	Short-Circuit Current	$T_J = 25^{\circ}\text{C}$		2.1			1.5			1.2		A
	Peak Output Current	$T_J = 25^{\circ}\text{C}$		2.4			2.4			2.4		A
	Average TC of V_{OUT}	$0^{\circ}\text{C} \leq T_J \leq +125^{\circ}\text{C}$, $I_O = 5 \text{ mA}$		0.6			1.5			1.8		mV/ $^{\circ}\text{C}$
V_{IN}	Input Voltage Required to Maintain Line Regulation	$T_J = 25^{\circ}\text{C}$, $I_O \leq 1\text{A}$		7.5			14.6			17.7		V


Note 1: Thermal resistance of the TO-3 package (K, KC) is typically $4^{\circ}\text{C}/\text{W}$ junction to case and $35^{\circ}\text{C}/\text{W}$ case to ambient. Thermal resistance of the TO-220 package (T) is typically $4^{\circ}\text{C}/\text{W}$ junction to case and $50^{\circ}\text{C}/\text{W}$ case to ambient.

Note 2: All characteristics are measured with capacitor across the input of $0.22 \mu\text{F}$, and a capacitor across the output of $0.1\mu\text{F}$. All characteristics except noise voltage and ripple rejection ratio are measured using pulse techniques ($t_w \leq 10 \text{ ms}$, duty cycle $\leq 5\%$). Output voltage changes due to changes in internal temperature must be taken into account separately.


Note 3: Absolute Maximum Ratings indicate limits beyond which damage to the device may occur. For guaranteed specifications and the test conditions, see Electrical Characteristics.

Typical Performance Characteristics


Maximum Average Power Dissipation




Maximum Average Power Dissipation




Peak Output Current




Output Voltage (Normalized to 1V at T_J = 25°C)



Ripple Rejection




Ripple Rejection




Typical Performance Characteristics (Continued)

Output Impedance




DS007746-11

Dropout Voltage




DS007746-12

Dropout Characteristics




DS007746-13

Quiescent Current




DS007746-14

Quiescent Current



DS007746-15


Physical Dimensions inches (millimeters) unless otherwise noted

KC02A (REV C)

Aluminum Metal Can Package (KC)
Order Number LM7805CK, LM7812CK or LM7815CK
NS Package Number KC02A

LM78XX Series Voltage Regulators

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



TO-220 Package (T)
Order Number LM7805CT, LM7812CT or LM7815CT
NS Package Number T03B

LIFE SUPPORT POLICY

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT AND GENERAL COUNSEL OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
 2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.



National Semiconductor Corporation
Americas
Tel: 1-800-272-9959
Fax: 1-800-737-7018
Email: support@nsc.com
www.national.com

National Semiconductor
Europe
Fax: +49 (0) 180-530 85 86
Email: europe.support@nsc.com
Deutsch Tel: +49 (0) 69 9508 6208
English Tel: +44 (0) 870 24 0 2171
Francais Tel: +33 (0) 1 41 91 8790

**National Semiconductor
Asia Pacific Customer
Response Group**
Tel: 65-2544466
Fax: 65-2504466
Email: ap.support@nsc.com

**National Semiconductor
Japan Ltd.**
Tel: 81-3-5639-7560
Fax: 81-3-5639-7507

This datasheet has been downloaded from:

www.DatasheetCatalog.com

Datasheets for electronic components.

National Semiconductor was acquired by Texas Instruments.

http://www.ti.com/corp/docs/investor_relations/pr_09_23_2011_national_semiconductor.html

This file is the datasheet for the following electronic components:

LM7815 - <http://www.ti.com/product/lm7815?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

7812 - <http://www.ti.com/product/7812?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

LM7815CK - <http://www.ti.com/product/lm7815ck?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

LM7812CK - <http://www.ti.com/product/lm7812ck?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

7815 - <http://www.ti.com/product/7815?HQS=TI-null-null-dscatalog-df-pf-null-wwe>

LM7805CK - <http://www.ti.com/product/lm7805ck?HQS=TI-null-null-dscatalog-df-pf-null-wwe>